

KIWO DEGREASER 1:40

1. DESCRIPTION

KIWO DEGREASER 1:40 is a highly concentrated cleaning and degreasing solution for use in automatic reclaiming machinery. It is suitable for all mesh types and prevents pinholes and irregularities in coating. KIWO DEGREASER 1:40 emulsifies dirt and grease thus making them water soluble. It is especially formulated for reduced foaming in machines.

2. APPLICATION

KIWO DEGREASER 1:40 can be reduced with water at a ratio of 1:40. Follow machine manufacturers directions. Tests should be carried out using the actual machine, as metering ratios vary. Set a thorough rinsing cycle after applying the degreaser solution.

It is recommended to degrease the screens as shortly before the screen is coated as possible, to eliminate contamination of the clean screen.

KIWO DEGREASER 1:40 can also be used for a degreasing cycle prior to decoating or reclaiming to remove oily residues from solvents and inks.

3. PHYSICAL DATA

Color:	Brownish-clear
Consistency:	Liquid
Shelflife:	1 year at 68 degrees Fahrenheit (20 degrees Celsius)
Flash point:	Not applicable
TLV:	Not applicable
VOC:	None
pH value:	9
HMS rating:	Health - 1 Flammability - 0 Reactivity - 0

4. PERSONAL PROTECTION

It is recommended to wear protective glasses and gloves. See Material Safety Data Sheet for additional information.

5. ENVIRONMENTAL PROTECTION

KIWO DEGREASER 1:40 solutions can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

6. PACKAGING

1 US quart, 1 US gallon, 5 US gallon containers

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.