

KIWOCLEAN AQ 508 STENCIL REMOVER concentrate

1. DESCRIPTION

KIWOCLEAN AQ 508 STENCIL REMOVER concentrate is a concentrated stencil removing solution for screens. It can be used in a dilution of up to 1:5 with water. KIWOCLEAN AQ 508 STENCIL REMOVER concentrate does not require the typical hazardous charge, required when shipping most concentrated stencil removers.

It is also used in combination with KIWO water based screen cleaners, e.g. KIWOCLEAN AQ 808 INK WASH concentrate. KIWOCLEAN AQ 508 STENCIL REMOVER concentrate solutions are colorless and free from chlorine.

KIWOCLEAN AQ 508 STENCIL REMOVER concentrate is suitable for use with all direct photo emulsions and capillary films, but not indirect films.

2. APPLICATION

For Use in Automatic Reclaiming Systems

General Instructions: Determine the capacity of the tank and calculate the required amounts of water, KIWOCLEAN AQ 808 INK WASH concentrate (808) and KIWOCLEAN AQ 508 STENCIL REMOVER concentrate (508). There should generally be two gallons of 808 for each gallon of 508.

For Plastisol and/or UV inks, begin with 5 gallons of water for each gallon of 508. A typical mixture would contain the following ratios of product:

508 Stencil Remover	1 gallon	12.5%
808 Ink Wash	2 gallons	25%
Water	5 gallons	62.5%
Working Solution	8 gallons	100%

For difficult to clean inks and/or for water resistant emulsions, use less water. A typical mixture would contain the following ratios of product:

508 Stencil Remover	1 gallon	20%
808 Ink Wash	2 gallons	40%
Water	2 gallons	40%
Working Solution	5 gallons	100%

For help with unusual inks or stencils, please contact KIWO, Inc. Technical Services department.

Mix the required amounts using suggested ratios above in the tank of the machine. It is useful to fill the tank only 90% full in initial testing to allow fine tuning the cleaning mixture for optimum results.

Notice: Never allow KIWOCLEAN AQ 508 STENCIL REMOVER concentrate solution to dry on a stenciled screen, as it will hardened the emulsion coating to the point it will be impossible to remove, or very difficult at best.

Ensure that decoating, coating and degreasing always take place in separate areas and at different times. During decoating, KIWOCLEAN a spray mist is produced which can settle on screens stored in the same room. When coating, the spray mist may cause

localized hardening of the photo emulsion which will remain in the open areas after developing.

For Manual Use Cleaning

Start by mixing 2 parts KIWOCLEAN AQ 508 STENCIL REMOVER concentrate with 4 parts of water. Then mix 1 part KIWOCLEAN AQ 808 INK WASH concentrate.

508 Stencil Remover	2 gallons	29%
808 Ink Wash	1 gallon	14%
Water	4 gallons	57%
Working Solution	7 gallons	100%

Test the mixture on a typical production screen.

NOTE: The solution needs to be stirred before each use. Once stirred, the solution will appear milky white in color.

If more reclaiming power is needed, add more KIWOCLEAN AQ 508 STENCIL REMOVER concentrate.

If more ink removing power is needed, add more KIWOCLEAN AQ 808 INK WASH concentrate.

If the solution needs to be more cost effective, add more water.

Continue to adjust the solution ratios until the required working solution is found. Record the final ratio and maintain the working solution.

The products need to be mixed within 1-2 weeks of use. If the working solution shows signs of less cleaning, add more KIWOCLEAN AQ 508 STENCIL REMOVER concentrate to boost the reclaiming – add more KIWOCLEAN AQ 808 INK WASH concentrate to boost the ink removing cleaning. Aging depends on the system and ratios used. Monitor aging and report concerns to KIWO.

3. PHYSICAL DATA

Color:	Colorless
Consistency:	Liquid
Shelf Life:	1 year at 20°- 25° Celsius
Flash Point:	None
pH value:	~2
TLV:	None
VOC:	None
Vapor Pressure:	Same as water
HMIS rating:	Health - 1 Flammability - 0 Reactivity - 0

4. PERSONAL PROTECTION

When working with KIWOCLEAN AQ 508 STENCIL REMOVER concentrate, wear safety gloves and goggles. Never allow KIWOCLEAN AQ 508 STENCIL REMOVER concentrate to dry on organic materials (e.g. cleaning rags made of paper, textile and various plastics) as this may cause self-ignition. If spray mist is produced, ensure sufficient extraction – do not breathe the fumes.

When mixed with KIWOCLEAN AQ 808 INK WASH concentrate, self ignition is possible if the active component of the decoating agent dries out and in case of reaction with organic substances. Observe the instructions given by the manufacturer and ensure that no drying is possible.

5. ENVIRONMENTAL PROTECTION

In usual working dilution, KIWOCLEAN AQ 508 STENCIL REMOVER concentrate solutions can safely be emptied into drains. Please follow further information given in the material safety data sheet.

6. PACKAGING

1 US quart, 1 US gallon, 5 US gallon containers, 55 US gallon drums

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. All products mentioned in this Technical Information are available through KIWO Inc. and its distributor network. For further information contact your authorized KIWO distributor or KIWO directly.

Thank you for choosing **KIWO**.