

PREGAN DL

1. DESCRIPTION

Pregan DL is a water emulsifiable solvent paste used to remove adhesive and lacquer residue from screen frames. All one and two component adhesives like KIWOBOND and ARCABOND adhesives and ESTELAN lacquers can easily be removed from steel and aluminium frames.

2. APPLICATION

Apply a layer approximately 1/16 inch thick of PREGAN DL onto the adhesive or lacquer residue to be removed. Let it react for approximately 5-10 minutes. Then scrape the softened residue from the frame using a knife or a spatula. Very stubborn residue may require the process to be repeated. Rinse off residual PREGAN DL with water.

3. PHYSICAL DATA

Color: Clear
Consistency: Paste
Shelflife: 1 year at 68° Fahrenheit (20° Celsius)
Flash point: 135° F
TLV: 10 ppm skin dimethyl acetamide
HMIS rating: Health - 2
Flammability - 1
Reactivity - 1

4. PERSONAL PROTECTION

Keep away from sources of ignition. Do not breathe fumes. Working areas must be well ventilated. Avoid contact with eyes and skin. Wear chemical-splash eye goggles and protective gloves. See Material Safety Data Sheet for additional information.

5. ENVIRONMENTAL PROTECTION

Do not empty into drains. Consult your local authorities for local regulations. See Material Safety Data Sheet for further information.

6. PACKAGING

750 gram container

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.