

## PREGASOL F

### 1. DESCRIPTION

PREGASOL F is a ready to use emulsion reclaimer liquid for decoating of polymer-based direct emulsions and capillary films such as Diazo- and SBQ-sensitized emulsions.

### 2. APPLICATION

Apply the PREGASOL F solution with a soft, clean brush evenly on both sides of the wet screen after the screen has been carefully cleaned of ink residue. Rub the screen gently with a brush to dissolve the emulsion.

After approximately 2 minutes, rinse thoroughly with a strong water spray. A high pressure water spray (1000 - 2000 psi, 40 - 60 bar) may be required for highly water resistant emulsions. Prolonged reaction times are possible and may help in the decoating process.

Ensure that the PREGASOL F solution does not dry on the screen. This can lead to a hardening of the emulsion and the resulting emulsion residues will be extremely difficult to remove.

### 3. PHYSICAL DATA

Color:	Green
Consistency:	Liquid
Shelflife:	1 year at 68° Fahrenheit
Flash point:	Not applicable
TLV:	Not applicable
VOC:	None
pH value:	>5
HMIS rating:	Health - 1 Flammability - 0 Reactivity - 0

### 4. PERSONAL PROTECTION

It is recommended to wear protective glasses and gloves. See Material Safety Data Sheet for additional information.

### 5. ENVIRONMENTAL PROTECTION

PREGASOL F can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

### 6. PACKAGING

1 US quart, 1 US gallon, 5 US gallon containers

### 7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at [www.kiwo.com](http://www.kiwo.com). For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.