

PREGASOL CF 20

1. DESCRIPTION

PREGASOL CF 20 concentrate is a concentrated emulsion reclaimer for decoating of polymer-based direct emulsions and capillary films such as Diazo- and SBQ-sensitized emulsions. PREGASOL CF 20 is a liquid concentrate which is diluted with 5 - 10 parts water for optimum efficiency. PREGASOL CF 20 concentrate does not crystallize when drying and is suitable for use in automatic reclaiming equipment.

2. APPLICATION

PREGASOL CF 20 concentrate has been formulated for dilution with 5 - 10 parts water.

Apply the diluted solution with a soft, clean brush evenly on both sides of the screen after the screen has been carefully cleaned of ink residue. Rub the screen gently with a brush to dissolve the emulsion.

After approximately 2 minutes, rinse thoroughly with a strong water spray. A high pressure water spray (1000 - 2000 psi, 40 - 60 bar) may be required for highly water resistant emulsions. Prolonged reaction time may result in reverse effects and does not help in the decoating process. Rather, rinse the screen and reapply fresh decoating solution.

Ensure that the diluted PREGASOL CF 20 concentrate solution does not dry on the screen. This can lead to a hardening of the emulsion and the resulting emulsion residues will be extremely difficult to remove.

For automatic equipment a dwell time of 60 -120 seconds after applying the decoating solution is sufficient. If not all emulsion is removed, a second reclaiming cycle should be used to completely remove the emulsion.

3. PHYSICAL DATA

Color:	Clear
Consistency:	Liquid
Shelflife:	1 year at 68° Fahrenheit (20° Celsius)
Flash point:	Not applicable
TLV:	Not applicable
VOC:	None
pH value:	<2
HMIS rating:	Health - 1 Flammability - 0 Reactivity - 0

4. PERSONAL PROTECTION

Protective glasses and gloves are recommended. See Material Safety Data Sheet for additional information.

5. ENVIRONMENTAL PROTECTION

PREGASOL CF 20 CONCENTRATE can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

6. PACKAGING

1 US quart, 1 US gallon, 5 US gallon containers

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.