

PREGASOL P

1. DESCRIPTION

PREGASOL P is a ready to use emulsion reclaimer for decoating of polymer-based direct emulsions and capillary films such as Diazo- and SBQ-sensitized emulsions. PREGASOL P is a odorless decoating paste for screens that require prolonged reaction time or where drying of liquid reclaimers is a concern.

2. APPLICATION

Apply the PREGASOL P solution with a soft, clean brush evenly on both sides of the wet screen after the screen has been carefully cleaned of ink residue. Rub the screen gently with a brush to dissolve the emulsion.

After approximately 2 minutes, rinse thoroughly with a strong water spray. A high pressure water spray (1000 - 2000 psi, 40 - 60 bar) may be required for highly water resistant emulsions. Prolonged reaction times are possible and may help in the decoating process.

Ensure that the PREGASOL P solution does not dry on the screen. This can lead to a hardening of the emulsion and the resulting emulsion residues will be extremely difficult to remove.

3. PHYSICAL DATA

| | |
|--------------|---|
| Color: | Pink |
| Consistency: | Paste |
| Shelflife: | 1 year at 68 degrees Fahrenheit (20 degrees celsius) |
| Flash point: | Not applicable |
| TLV: | Not applicable |
| VOC: | None |
| pH value: | >5 |
| HMS rating: | Health - 1 Flammability - 0 Reactivity - 0 |

4. PERSONAL PROTECTION

It is recommended to wear protective glasses and gloves. See Material Safety Data Sheet for additional information.

5. ENVIRONMENTAL PROTECTION

PREGASOL P can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

6. PACKAGING

1 US quart, 1 US gallon, 5 US gallon containers

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at www.kiwo.com. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing **KIWO**.