

KIWOMIX[®] Z8 10, \$

Special defoaming agent for automatic reclaim and degreasing units

KIWOMIX ZD 1080 is a defoaming agent. It is used in the re-circulating tanks of automatic reclaim and degreasing units.

APPLICATION

Use a spray bottle and spritz onto the surface of the foam to disperse the foam if needed. Depending on the amount of foam, it can be added directly into the chemical tank at a ration 0.1 % up to max. 0.5% of KIWOMIX ZD 1080. This means that 100 ml up to max. 500 ml of KIWOMIX ZD 1080 are added to 100 liters of re-circulating water and are mixed well by stirring.

It is advisable to dilute the required quantity of defoaming agent with 5 times the quantity of water. This mixture can easily be added to the foaming water. Please note that these defoaming dilutions are only stable for a short time.

PRODUCT DATA

Color: White
Consistency: Liquid

HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION

Due to its formulation, KIWOMIX ZD 1080 does not need any labeling. Nevertheless, we recommend to observe the usual precautions when working with chemicals (protective goggles and gloves).

For environmental reasons, KIWOMIX ZD 1080 does not contain any dyes or perfumes.

Please follow further information given in the material safety data sheet.

STORAGE

2 years (at 20 - 25°C and tightly closed original container)

Protect against freezing

After a longer period of storage a separation of the product is possible, it can be eliminated by stirring or shaking.